

**Global Parts Order Processing
Material Safety Data Sheet
DWAYNE LANE'S CHRYSLER JEEP**

C H R Y S L E R
HAZARD COMMUNICATION SHEET

1004551 DRAFT PART/COMMTY CD: 68043526AA
PREPARATION DATE: 11-30-09 STNDRD: N/AV SUPPLIER: 26724 MFGR: 03500
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: MOPAR HEADLIGHT RESTORATION KIT STEP 1
MFG ID : A42
DESCRIPTION: HEADLAMP RESTORER-KIT

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS: PERCENT
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS
EXISTING INGREDIENTS
MINERAL SPIRITS RULE 66 10-30 W 300 300 100 PPM
064742-47-8 MINERAL SPIRITS RULE L 400 N/AP 400
KAOLIN 10-30 W 10 2 2 MG/M3
001332-58-7 KAOLIN
WATER 30-60 W N/AP N/AP N/AP N/AP
007732-18-5 WATER (8CI9CI)
SOUTHERN BENTONITE 1-5 W N/AP N/AP N/AP N/AP
001302-78-9 SOUTHERN BENTONITE
GENERIC DESC: MIXTURE(S) OF THE FOLLOWING: ALIPHATIC HYDROCARBON(S) AND
PETROLEUM DISTILLATE(S).

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : 300 TO 500 F SOLUB IN WATER: NEGLIGIBLE (< 0.1%)
VAPOR PRESSURE: < 1 MM HG ATN/AP EVAP. RATE: < 1.000 REF: BUTYLACETATE
VAPOR DENSITY : > 1.000 AT N/AP SPECIFIC GRAVITY: 1.160 AT 60 F
PH AT FULL STRENGTH: 8.5 PH AT REC. DILUT: N/AV
%VOLATILE BY VOL : N/AV VOLATILE ORGANIC COMP: N/AV N/AV
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV
APPEARANCE & ODOR: APPEARANCE: CLEAR..... COLOR: AMBER..... STATE: LIQUID.....
ODOR: PETROLEUM.....

**Global Parts Order Processing
Material Safety Data Sheet
DWAYNE LANE'S CHRYSLER JEEP**

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

FLASH POINT: 142 F PMCC IGN TEMP: N/AV LEL: N/AV UEL: N/AV

SPECIAL FIRE & EXPLOSION HAZARDS:

VAPOR MAY FORM AN EXPLOSIVE MIXTURE WITH AIR. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY ON HOT SURFACES.

EXTINGUISHING MEDIA:

WATER, DRY CHEMICAL, CARBON DIOXIDE OR FOAM.

SPECIAL FIREFIGHTING PROCEDURES:

USE PROTECTIVE CLOTHING. USE SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

SENSITIVE TO MECHANICAL IMPACT?: N/AV SENSITIVE TO STATIC DISCHARGE?: N/AV

HAZARDOUS COMBUSTION PRODUCTS:

TOXIC FUMES OR VAPORS, CARBON MONOXIDE AND CARBON DIOXIDE.

FLAME PROJECTION: N/AV

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---INHALATION--->> VAPOR AND/OR MIST MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT. HIGH CONCENTRATION MAY PRODUCE THE FOLLOWING: ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING, CONFUSION, UNCONSCIOUSNESS OR COMA. <<---SKIN CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: PRIMARY IRRITATION. PROLONGED SKIN EXPOSURE MAY RESULT IN THE FOLLOWING: DEFATTING AND DRYING OF SKIN. <<---EYE CONTACT--->> IRRITATION AND REDNESS. <<---INGESTION--->> MAY BE HARMFUL IF SWALLOWED. MAY CAUSE UPSET STOMACH, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION (GOING DOWN THE WRONG PIPE INTO THE WINDPIPE) MAY CAUSE THE FOLLOWING: PULMONARY CHANGES.

EMERGENCY FIRST AID PROCEDURES:

<<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. IF BREATHING IS DIFFICULT, GIVE OXYGEN. ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. CARDIAC RESUSCITATION IF INDICATED. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---SKIN CONTACT--->> REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. REMOVE CONTACT LENSES TO ASSURE COMPLETE FLUSHING. CONTACT A PHYSICIAN. <<---INGESTION--->> DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT LIQUID FROM SEEPING INTO THE WINDPIPE AND LUNGS.

*** SECTION 06 - REACTIVITY DATA ***

**Global Parts Order Processing
Material Safety Data Sheet
DWAYNE LANE'S CHRYSLER JEEP**

STABILITY: STABLE

CONDITIONS TO AVOID:

HIGH TEMPERATURE, SPARKS OR OPEN FLAME.

MATERIALS TO AVOID:

STRONG OXIDIZING AGENTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION MAY PRODUCE THE FOLLOWING: TOXIC FUMES OR VAPORS,
CARBON MONOXIDE AND CARBON DIOXIDE.

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

WEAR PROTECTIVE CLOTHING. AVOID BREATHING VAPORS. VENTILATE AREA.
ELIMINATE ALL IGNITION SOURCES (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC
OR FRICTIONAL SPARKS). CONTAIN WITH EARTH OR SAND TO PREVENT ENTERING
DRAINS. ABSORB ON AN INERT MATERIAL. DISCARD INTO SEALED CONTAINERS FOR
DISPOSAL. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS,
WATERCOURSES OR EXTENSIVE LAND AREAS.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND
FEDERAL DISPOSAL REGULATIONS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. IF THE ALLOWABLE
LIMIT OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, USE THE FOLLOWING:
ORGANIC VAPOR RESPIRATOR.

VENTILATION TYPE:

TO MAINTAIN THE TLV, THE FOLLOWING MAY BE NEEDED: GOOD GENERAL VENTILATION
AND/OR LOCAL EXHAUST VENTILATION.

PROTECTIVE GLOVES:

RECOMMENDED. THE FOLLOWING IS REQUIRED: NEOPRENE GLOVES OR NITRILE RUBBER
GLOVES.

EYE PROTECTION:

RECOMMENDED. THE FOLLOWING IS REQUIRED: SAFETY GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE EQUIPMENT:

AVOID PROLONGED SKIN CONTACT. PREVENT PROLONGED SKIN CONTACT WITH
CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSE. A SAFETY
SHOWER MAY BE NEEDED FOR EMERGENCY SITUATIONS. AN EYE WASH MAY BE NEEDED FOR
EMERGENCY SITUATIONS.

*** SECTION 09 - SPECIAL PRECAUTIONS ***

**Global Parts Order Processing
Material Safety Data Sheet
DWAYNE LANE'S CHRYSLER JEEP**

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE IN A COOL, DRY PLACE. STORE IN A WELL VENTILATED AREA. STORE SEPARATE FROM INCOMPATIBLE MATERIALS. USE WITH ADEQUATE VENTILATION. KEEP FROM HEAT, SPARK OR OPEN FLAMES. REACTS WITH OXIDIZERS. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. DO NOT STORE IN OPEN OR UNLABELED CONTAINERS.

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING VAPOR. AVOID SKIN CONTACT. AVOID EYE CONTACT. AVOID INGESTION. DO NOT SMOKE OR EAT WHEN HANDLING THIS SUBSTANCE; WASH THOROUGHLY AFTER USING. WASH THOROUGHLY AFTER HANDLING. MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP
NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

INFORMATION UNAVAILABLE AT THIS TIME