

SECTION I

FEB 13 1986

PRODUCT NAME OR NUMBER: RTV SEALANT - PRESSURIZED CONTAINER 9475
BLUE

MOTOR VEHICLE

MANUFACTURERS NAME: THE OEC CORPORATION
ADDRESS: P.O. Box 1068 (44258) 667 Lafayette Rd Medina, Ohio 44222
PHONE: (216) 725-0001

PROPER SHIPPING NAME(49 CFR 172.101): CONSUMER COMMODITY
D.O.T. HAZARD NAME (49 CFR 172.101) COMPRESSED GAS
D.O.T. ID NO(49 CFR 172.101): 1956
D.O.T. HAZARD CLASS (49 CFR 172.101): ORM-D
RCRA HAZARD CLASS*(40 CFR 261): NONE
E.P.A. PRIORITY POLLUTANTS (40 CFR 122.53): NONE
HEALTH (NFPA): 1 FLAMABILITY (NFPA): 1 REACTIVITY (NFPA): 1
CAS.NO.: MIXTURE
GENERIC DESCRIPTION: SILICONE

* IF DISCARDED

SECTION II HAZARDOUS INGREDIENTS

Acetoxysilane	5 %	TLV (units): 10 ppm* * Based on Acetic Acid.
---------------	-----	---

SECTION III HEALTH HAZARD DATA HEALTH (NFPA) 1

EFFECTS OF OVEREXPOSURE: Irritates eyes. Prolonged or repeated contact may irritate in.

THRESHOLD LIMIT VALUE OF PRODUCT: 10 ppm (based on liberated acetic acid)

EMERGENCY AND FIRST AID PROCEDURES: Wipe off. Flush with water. Obtain medical attention for eyes if necessary.

SECTION IV FIRE AND EXPLOSION HAZARD DATA FLAMMABILITY (NFPA) 1

FLASH POINT (Method Used): Open Cup above 250° F/120° C
FLAMMABLE LIMITS IN AIR, % BY VOLUME: Lower: Not applicable
Upper: Not applicable

EXTINGUISHING MEDIA: Carbon dioxide or foam.

SPECIAL FIRE FIGHTING PROCEDURES: Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. High Temperatures may cause the container to rupture.

SECTION V PHYSICAL DATA

BOILING POINT: Above 300° F/149° C
SPECIFIC GRAVITY: 1.05
MELTING POINT: Not applicable
VAPOR PRESSURE: Less than 5 mm (RTV); 70 psig for pressurizing agent
VAPOR DENSITY (AIR=1): Not applicable
PERCENT VOLATILE BY VOLUME (%): Less than 5%
EVAPORATION RATE (ether =1): Less than 1
SOLUBILITY IN WATER (%): Less than 0.1%
FLASH POINT (method used): Open Cup above 250° F/120° C.
ODOR, APPEARANCE, COLOR: Acetic acid-like, paste, various.

SECTION VI REACTIVITY DATA

REACTIVITY (NFPA) 1

STABILITY: STABLE

CONDITIONS TO AVOID: AIR OR MOISTURE CAUSES POLYMERIZATION AND ACETIC ACID VAPORS ARE FORMED.

COMPATIBILITY (MATERIALS TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION. HAZARDOUS DECOMPOSITION PRODUCTS: SILICON DIOXIDE, CARBON DIOXIDE, AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE

SECTION VII SPILL, LEAK AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: USE ABSORBENT MATERIAL TO REMOVE AND CONTAIN FOR SALVAGE OR DISPOSAL.

D.O.T. (49 CFR 171.8)/E.P.A. (40 CFR 117) SPILL REPORTING INFORMATION

HAZARDOUS SUBSTANCE: NONE

RQ: NOT APPLICABLE

CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE

REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

SECTION VII SPECIAL PROTECTION INFORMATION

LABORATORY PROTECTION (SPECIFY TYPE): ACID VAPOR TYPE.

RESPIRATION

LOCAL EXHAUST: NONE SHOULD BE NEEDED.

SPECIAL: NONE KNOWN TO BE REQUIRED

MECHANICAL (GENERAL): RECOMMENDED.

OTHER: NONE KNOWN TO BE REQUIRED

PROTECTIVE GLOVES: RUBBER PLASTIC RECOMMENDED.

EYE PROTECTION: PROPER EYE PROTECTION SHOULD BE WORN IN ANY TYPE OF INDUSTRIAL OPERATION.

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE BELOW 120°F/49 C
USE REASONABLE CARE.

OTHER PRECAUTIONS: NONE KNOWN TO BE REQUIRED

HAZARD: NONE

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL PRACTICES AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.