



## SAFETY DATA SHEET

in accordance with 1907/2006/EC (REACH, as amended by 2015/830/EU) 29 CFR 1910.1200 and WHMIS 2015

**Revision date:** 29 December 2020

**Initial date of issue:** 29 March 2007

**SDS No.** 220A-14c

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

995 Release Agent (Aerosol)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

A highly effective, CFC-free release agent formulated for use in all mold applications ranging from sand core operations and investment casting to hard-to-release molding procedure with polyurethanes, rubber, filled thermoplastics and composites.

#### 1.3. Details of the supplier of the safety data sheet

##### Company:

A.W. CHESTERTON COMPANY  
860 Salem Street  
Groveland, MA 01834-1507, USA  
Tel. +1 978-469-6446 Fax: +1 978-469-6785  
(Mon. - Fri. 8:30 - 5:00 PM EST)  
SDS requests: [www.chesterton.com](http://www.chesterton.com)  
E-mail (SDS questions): [ProductMSDSs@chesterton.com](mailto:ProductMSDSs@chesterton.com)  
E-mail: [customer.service@chesterton.com](mailto:customer.service@chesterton.com)

##### Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,  
Unit 105, Burlington, Ontario L7L 4X8 - Tel. 905-335-5055  
EU: Chesterton International GmbH, Am Lenzenfleck 23,  
D85737 Ismaning, Germany – Tel. +49-89-996-5460

#### 1.4. Emergency telephone number

24 hours per day, 7 days per week  
Call Infotrac: 1-800-535-5053  
Outside N. America: +1 352-323-3500 (collect)  
NSW Poisons Information Centre (Australia): 13 11 26

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### 2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 1, H222, H229  
Skin Irrit. 2, H315  
STOT SE 3, H336  
Aquatic Chronic 2, H411

##### 2.1.2. Classification according to 29 CFR 1910.1200 / WHMIS 2015

Flam. Aerosol 1, H222  
Press. Gas (Comp.), H280  
Skin Irrit. 2, H315  
STOT SE 3, H336  
Aquatic Chronic 2, H411

##### 2.1.3. Australian statement of hazardous nature

Hazardous according to criteria of Safe Work Australia.

##### 2.1.4. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

**2.2. Label elements****2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]****Hazard pictograms:****Signal word:**

Danger

**Hazard statements:**

H222 Extremely flammable aerosol.  
 H229 Pressurized container: May burst if heated.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe vapours/spray.  
 P262 Do not get in eyes, on skin, or on clothing.  
 P264 Wash skin thoroughly after handling.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

**Supplemental information:** None**2.2.2. Labelling according to 29 CFR 1910.1200 / WHMIS 2015****Hazard pictograms:****Signal word:**

Danger

**Hazard statements:**

H222 Extremely flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe vapours/spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves.  
 P302/352 IF ON SKIN: Wash with plenty of soap and water.  
 P304/340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P332/313 If skin irritation occurs: Get medical advice/attention.  
 P362/364 Take off contaminated clothing and wash it before reuse.  
 P403 Store in a well-ventilated place.  
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container to an approved waste disposal plant.

**Supplemental information:** None**2.3. Other hazards**

None known

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

Hazardous Ingredients <sup>1</sup>	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Naphtha (petroleum), light alkylate*	50-60	64741-66-8 265-068-8	NA	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Propane	30-40	74-98-6 200-827-9	NA	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Simple Asphyx.

For full text of H-statements: see SECTION 16.

\* Contains less than 0.1 % w/w Benzene.

<sup>1</sup> Classified according to: \* 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), California Proposition 65  
\* 1272/2008/EC, GHS, REACH  
\* WHMIS 2015  
\* Safe Work Australia

**SECTION 4: FIRST AID MEASURES****4.1. Description of first aid measures**

**Inhalation:** Remove to fresh air. If not breathing, administer artificial respiration. Contact physician.

**Skin contact:** Wash skin with soap and water. Take off contaminated clothing and wash it before reuse. Contact physician if irritation persists.

**Eye contact:** Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.

**Ingestion:** Do not induce vomiting. If conscious, drink large quantities of water. Contact physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Prolonged or repeated skin contact may defat the skin and cause skin irritation. Direct contact may cause mild eye irritation. Vapor concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

**SECTION 5: FIREFIGHTING MEASURES****5.1. Extinguishing media**

**Suitable extinguishing media:** Carbon dioxide, dry chemical, foam or water spray

**Unsuitable extinguishing media:** Water jets

**5.2. Special hazards arising from the substance or mixture**

Pressurized containers, when heated, are a potential explosive hazard.

**5.3. Advice for firefighters**

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

**Flammability Classification:** NFPA: Storage Level III; 16 CFR 1500.3 Extremely flammable aerosol

**HAZCHEM Emergency Action Code:** 2 Y

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

**6.2. Environmental Precautions**

Keep out of sewers, streams and waterways.

**6.3. Methods and material for containment and cleaning up**

Contain spill to a small area. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

**6.4. Reference to other sections**

Refer to section 13 for disposal advice.

**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No Smoking. Utilize exposure controls and personal protection as specified in Section 8. Wash skin thoroughly after handling. Vapors are heavier than air and will collect in low areas. Vapor accumulations could flash and/or explode if ignited.

**7.2. Conditions for safe storage, including any incompatibilities**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (120°F). Do not pierce or burn, even after use.

**7.3. Specific end use(s)**

No special precautions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL <sup>1</sup>		ACGIH TLV <sup>2</sup>		UK WEL <sup>3</sup>		AUSTRALIA ES <sup>4</sup>	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Naphtha (petroleum), light alkylate*	–	–	–	–	–	–	–	–
Propane	1000	1800	**	–	–	–	–	–

\* Chesterton recommended limit: 241 ppm, 1200mg/m<sup>3</sup>. \*\*Simple asphyxiant.

<sup>1</sup> United States Occupational Health & Safety Administration permissible exposure limits

<sup>2</sup> American Conference of Governmental Industrial Hygienists threshold limit values

<sup>3</sup> EH40 Workplace exposure limits, Health & Safety Executive

<sup>4</sup> Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003]

**Derived No Effect Level (DNEL) according to Regulation (EC) No 1907/2006:****Workers**

Substance	Route of exposure	Potential health effects	DNEL
Hydrocarbons, C7-C9, isoalkanes	Inhalation	Chronic effects, systemic	2035 mg/m <sup>3</sup>
	Dermal	Chronic effects, systemic	773 mg/kg bw/day

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No 1907/2006:**

Not available

**8.2. Exposure controls****8.2.1. Engineering measures**

Use only in well-ventilated areas. If necessary, provide explosion-proof ventilation.

**8.2.2. Individual protection measures**

**Respiratory protection:** Not normally needed. If exposure limits are exceeded, use approved organic vapor respirator (e.g., EN filter type A/P).

**Protective gloves:** Chemical resistant gloves (e.g. Viton\*, neoprene, nitrile). \*DuPont's registered trademark.

**Eye and face protection:** Safety glasses

**Other:** Impervious clothing (e.g. Viton\*, neoprene or nitrile) as necessary to prevent skin contact.

**8.2.3. Environmental exposure controls**

Refer to sections 6 and 12.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	low viscosity liquid	<b>Odour</b>	mild petroleum odor
<b>Colour</b>	clear	<b>Odour threshold</b>	not determined
<b>Initial boiling point</b>	116°C (240°F), product only	<b>Vapour pressure @ 20°C</b>	54 mm Hg
<b>Melting point</b>	not applicable	<b>% Aromatics by weight</b>	0%
<b>% Volatile (by volume)</b>	94.5%	<b>pH</b>	not applicable
<b>Flash point</b>	< 7°C (<45°F)	<b>Relative density</b>	0.6 kg/l
<b>Method</b>	PM Closed Cup, product only	<b>Weight per volume</b>	5.3 lbs/gal.
<b>Viscosity</b>	< 100 cps @ 25°C	<b>Coefficient (water/oil)</b>	< 1
<b>Autoignition temperature</b>	not determined	<b>Vapour density (air=1)</b>	> 1
<b>Decomposition temperature</b>	no data available	<b>Rate of evaporation (ether=1)</b>	< 1
<b>Upper/lower flammability or explosive limits</b>	LEL: 1.2; UEL: 9.9	<b>Solubility in water</b>	< 1%
<b>Flammability (solid, gas)</b>	extremely flammable (propellant)	<b>Oxidising properties</b>	not determined
<b>Explosive properties</b>	not determined		

**9.2. Other information**

None

**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

Refer to sections 10.3 and 10.5.

**10.2. Chemical stability**

Stable

**10.3. Possibility of hazardous reactions**

No dangerous reactions known under conditions of normal use.

**10.4. Conditions to avoid**

Open flames and red hot surfaces.

**10.5. Incompatible materials**

Strong oxidizers like liquid Chlorine and concentrated Oxygen.

**10.6. Hazardous decomposition products**

Carbon Monoxide, aldehydes and other toxic fumes (by combustion).

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

**Primary route of exposure under normal use:** Inhalation, skin and eye contact. Personnel with pre-existing skin and lung disorders are generally aggravated by exposure.

**Acute toxicity -**

**Oral:** Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Naphtha (petroleum), light alkylate	LD50, rat	> 5000 mg/kg

**Dermal:** Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Naphtha (petroleum), light alkylate	LD50, rabbit	> 2000 mg/kg

**Inhalation:**

Substance	Test	Result
Naphtha (petroleum), light alkylate	LC50, rat, 4 hours	> 21 mg/l (vapor)
Propane	LC50, rat, 4 hours	658 mg/l

**Skin corrosion/irritation:** Causes skin irritation.

Substance	Test	Result
Naphtha (petroleum), light alkylate	Skin irritation, rabbit	Moderate irritation

**Serious eye damage/irritation:** May cause mild eye irritation.

**Respiratory or skin sensitisation:**

Substance	Test	Result
Naphtha (petroleum), light alkylate	Skin sensitization, OECD 406	Not sensitizing

**Germ cell mutagenicity:** Naphtha (petroleum), light alkylate: not expected to be a germ cell mutagen, based on test data.

**Carcinogenicity:** As per 29 CFR 1910.1200 (Hazard Communication), this product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or Regulation (EC) No 1272/2008.

**Reproductive toxicity:** Naphtha (petroleum), light alkylate: not expected to be a reproductive toxicant, based on data from similar materials.

**STOT-single exposure:** May cause drowsiness or dizziness.

**STOT-repeated exposure:** Naphtha (petroleum), light alkylate: not expected to cause organ damage from prolonged or repeated exposure, based on test data.

**Aspiration hazard:** Not classified as an aspiration toxicant due to the aerosol spray pattern.

**Other information:** None known

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

### 12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment, based on data from similar materials.

### 12.2. Persistence and degradability

Naphtha (petroleum), light alkylate: expected to be inherently biodegradable (ready biodegradability, 28 days: 22%). Naphtha (petroleum), light alkylate, Propane: expected to degrade rapidly in air.

### 12.3. Bioaccumulative potential

Propane: bioconcentration in aquatic organisms is not expected to be significant.

### 12.4. Mobility in soil

Liquid. Solubility in water: < 1%. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). The hazardous ingredients will rapidly evaporate to the air if released into the environment.

### 12.5. Results of PBT and vPvB assessment

Not available

### 12.6. Other adverse effects

None known

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Incinerate absorbed material in an approved area. Incinerate pressurized containers at an approved facility. Check local, state and national/federal regulations and comply with the most stringent requirement. This product is classified as a hazardous waste according to 2008/98/EC.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

<b>ADR/RID/ADN/IMDG/ICAO:</b>	UN1950
<b>TDG:</b>	UN1950
<b>US DOT:</b>	UN1950

### 14.2. UN proper shipping name

<b>ICAO:</b>	Aerosols, Flammable
<b>IMDG:</b>	Aerosols
<b>ADR/RID/ADN:</b>	Aerosols, <i>flammable</i>
<b>TDG:</b>	Aerosols, <i>flammable</i>
<b>US DOT:</b>	Aerosols, <i>flammable</i>

**14.3. Transport hazard class(es)**

ADR/RID/ADN/IMDG/ICAO: 2.1  
 TDG: 2.1  
 US DOT: 2.1

**14.4. Packing group**

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE  
 TDG: NOT APPLICABLE  
 US DOT: NOT APPLICABLE

**14.5. Environmental hazards**

NO ENVIRONMENTAL HAZARDS

**14.6. Special precautions for user**

NO SPECIAL PRECAUTIONS FOR USER

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

NOT APPLICABLE

**14.8. Other information**

**US DOT:** Shipped as Limited Quantity in packaging having a rated capacity gross weight of 66 lb. or less (49 CFR 173.306(a),(3),(i)). ERG NO. 126  
**IMDG:** EmS. F-D, S-U, Shipped as Limited Quantity  
**ADR:** Classification code 5F, Tunnel restriction code (E), Shipped as Limited Quantity

**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

**Authorisations under Title VII:** Not applicable

**Restrictions under Title VIII:** None

**Other EU regulations:** Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers. Directive 94/33/EC on the protection of young people at work Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances (Petroleum products, qualifying quantities: 2 500 t, 25 000 t).

**15.1.2. National regulations****US EPA SARA TITLE III**

<b>312 Hazards:</b>	<b>313 Chemicals:</b>
Immediate	None
Fire	
Pressure Release	

**Other national regulations:** National implementation of the EC Directive referred to in section 15.1.1.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**SECTION 16: OTHER INFORMATION**

**Abbreviations and acronyms:** ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE: Acute Toxicity Estimate  
 BCF: Bioconcentration Factor  
 cATpE: Converted Acute Toxicity point Estimate  
 CLP: Classification Labelling Packaging Regulation (1272/2008/EC)  
 ES: Exposure Standard  
 GHS: Globally Harmonized System  
 ICAO: International Civil Aviation Organization  
 IMDG: International Maritime Dangerous Goods  
 LC50: Lethal Concentration to 50 % of a test population  
 LD50: Lethal Dose to 50% of a test population  
 LOEL: Lowest Observed Effect Level  
 N/A: Not Applicable  
 NA: Not Available  
 NOEC: No Observed Effect Concentration  
 NOEL: No Observed Effect Level  
 OECD: Organization for Economic Co-operation and Development  
 PBT: Persistent, Bioaccumulative and Toxic substance  
 (Q)SAR: Quantitative Structure-Activity Relationship  
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)  
 REL: Recommended Exposure Limit  
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail  
 SDS: Safety Data Sheet  
 STEL: Short Term Exposure Limit  
 STOT RE: Specific Target Organ Toxicity, Repeated Exposure  
 STOT SE: Specific Target Organ Toxicity, Single Exposure  
 TDG: Transportation of Dangerous Goods (Canada)  
 TWA: Time Weighted Average  
 US DOT: United States Department of Transportation  
 vPvB: very Persistent and very Bioaccumulative substance  
 WEL: Workplace Exposure Limit  
 WHMIS: Workplace Hazardous Materials Information System  
 Other abbreviations and acronyms can be looked up at [www.wikipedia.org](http://www.wikipedia.org).

**Key literature references and sources for data:** Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)  
 Chemical Classification and Information Database (CCID)  
 European Chemicals Agency (ECHA) - Information on Chemicals  
 Hazardous Chemical Information System (HCIS)  
 National Institute of Technology and Evaluation (NITE)  
 Swedish Chemicals Agency (KEMI)  
 U.S. National Library of Medicine Toxicology Data Network (TOXNET)

**Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP]:**

Classification	Classification procedure
Aerosol 1, H222	On basis of components
STOT SE 3, H336	Calculation method
Skin Irrit. 2, H315	Calculation method
Aquatic Chronic 2, H411	Calculation method

**Relevant H-statements:** H220: Extremely flammable gas.  
 H225: Highly flammable liquid and vapour.  
 H280: Contains gas under pressure; may explode if heated.  
 H315: Causes skin irritation.  
 H304: May be fatal if swallowed and enters airways.  
 H336: May cause drowsiness or dizziness.  
 H411: Toxic to aquatic life with long lasting effects.

**Hazard pictogram names:** Flame, gas cylinder (non-CLP labelling) exclamation mark, environment

**Changes to the SDS in this revision:** Section 14.8.

**Revision date:** 29 December 2020

**Further information:** None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.

