

Item# 29185

ITEM: 4UK03 - SEALANT PIPE 1/2 PINT

PICK REQ: 1010638393

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: A3611

This MSDS should be attached or kept with the respective product with which it is associated.

\*\*\*\*\* MATERIAL SAFETY DATA SHEET - A3611 \*\*\*\*\*

Associated Grainger Item: 4UK03 - SEALANT PIPE 1/2 PINT

A  
ANTI-SEIZE TECHNOLOGY  
A.S.T. INDUSTRIES, INC.

H.M.I.S.:  
H - 1  
F - 1  
R - 0  
P.P.

SOF-SET(TM)

GENERAL PURPOSE THREAD SEALANT  
STOCK #('S): 29002,29010,29016,29018,29025,29026,29030,29050,29055

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURE:  
ANTI-SEIZE TECHNOLOGY  
2345 N. 17TH. AVE.  
FRANKLIN PARK, IL. 60131

TELEPHONE #: 847-455-2300  
24 HOUR EMERGENCY #: INFOTRAC, 1-800-535-5053

SECTION II - HAZARDOUS INGREDIENTS

	CAS #	OSHA PEL, TLV	SARA III PROP 65, PERCENT
PETROLEUM DISTILLATES (EXEMPT MINERAL SPIRITS)	8002-05-9	100PPM	NO
		100PPM	NO
			23

SECTION III - PHYSICAL PROPERTIES

BOILING POINT: DOES NOT APPLY  
SOLUBILITY IN WATER: NIL  
MELTING POINT: DOES NOT APPLY  
RELATIVE HUMIDITY IN WATER: NONE  
VAPOR DENSITY: 5.2  
SPECIFIC GRAVITY: 1.3  
EVAPORATION RATE: 0.08  
PERCENT VOLATILE: 23  
VAPOR PRESSURE: LESS THAN 1 MMHG  
APPEARANCE AND ODOR: TAN/YELLOW PASTE, SLIGHT ODOR

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT AND METHOD USED:  
FOR SOLVENT 144 F., OF DRIED COMPOUND: OVER 500F. C.O.C.  
FLAMMABLE LIMITS:  
LEL: 1.0  
UEL: 7.0  
EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL  
SPECIAL FIRE FIGHTING PROCEDURES:  
THIS COMPOUND WILL NOT BURN UNLESS IT IS PRE-HEATED. WATER FOG MAY BE USED TO COOL THE CONTAINERS BUT DO NOT SPRAY DIRECTLY INTO LARGE CONTAINERS OF BURNING LIQUIDS AS FROTHING MAY OCCUR. WEAR A "N.I.O.S.H." APPROVED ORGANIC VAPOR RESPIRATOR.

UNUSUAL FIRE AND EXPLOSION HAZARDS:  
DENSE SMOKE AND NOXIOUS OR TOXIC FUMES MAY BE GENERATED IN A FIRE. FIRE FIGHTERS SHOULD WEAR A SELF CONTAINED BREATHING APPARATUS.

SECTION V - PHYSICAL HAZARDS

STABILITY:  
(X) STABLE  
( ) UNSTABLE  
CONDITIONS TO AVOID:  
STRONG OXIDIZING AGENT. NOT INTENDED FOR USE WITH OXYGEN  
INCOMPATIBILITY, (MATERIALS TO AVOID): OXYGEN SERVICE.  
HAZARDOUS DECOMPOSITION PRODUCTS:  
THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDANT UPON THE COMBUSTION CONDITIONS. NOXIOUS OR TOXIC FUMES MAY BE GENERATED, SOME OF WHICH MAY BE IRRITATING.  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARDS AND FIRST AID

ROUTES OF ENTRY:  
(X) SKIN

( ) EYES  
(X) INHALATION  
( ) INGESTION

HEALTH HAZARDS:  
THE SOLVENT USED IN THIS PRODUCT EVAPORATES VERY SLOWLY, AND THE AMOUNT OF PRODUCT USED IS RELATIVELY SMALL. THEREFORE IS NOT EXPECTED TO PRESENT AN INHALATION HAZARD UNDER NORMAL CONDITIONS OF USE. THE SOLVENT CAN BE IRRITATING TO THE SKIN, EYES OR RESPIRATORY TRACT, IF THE EXPOSURE IS HIGH ENOUGH. POSSIBLE SYMPTOMS COULD INCLUDE SKIN REDNESS, DRY CHAPPED SKIN, BURNING EYES, OR MILD COUGH. LONG TERM EXPOSURE (YEARS) OF HIGH EXPOSURE COULD LEAD TO A CONDITION KNOWN AS "PAINTERS SYNDROME"

EMERGENCY FIRST AID PROCEDURES:

SKIN:  
WASH WITH SOAP AND WATER, USING A NAIL BRUSH. PAY PARTICULAR ATTENTION TO FINGER NAILS AND OPEN WOUNDS.

EYES:  
THIS PRODUCT COULD CAUSE SOME MECHANICAL IRRITATION IF GOTTEN INTO THE EYES AND RUBBED. FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS. IF IRRITATION PERSISTS CONSULT A PHYSICIAN.

INGESTION:  
IF INGESTED THIS PRODUCT IS NOT EXPECTED TO CAUSE AN ACUTE REACTION. THIS PRODUCT CONTAINS A PETROLEUM DISTILLATE, DO NOT INDUCE VOMITTING, BECAUSE THE SOLVENT MAY BE ASPIRATED INTO THE LUNGS. USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN.

INHALATION:  
NOT LIKELY UNDER NORMAL CONDITIONS OF USE. IF USING IN HIGH TEMPERATURE APPLICATIONS WHERE THERMAL DECOMPOSITION IS LIKELY, USE A LOCAL EXHAUST TO REMOVE FUMES. IF DIZZINESS OR IRRITATION OCCURS, SEEK FRESH AIR.

CHEMICAL('S) LISTED AS CARCINOGENS:

NTP?:  
NO

I.A.R.C.?:  
NO

OSHA?:  
NO

SECTION VII - SPECIAL PRECAUTIONS AND SPILL PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:  
STORE IN CLOSED CONTAINERS AWAY FROM INTENSE HEAT OR OPEN FLAMES.

OTHER PRECAUTIONS:  
DO NOT TRANSFER TO UNMARKED CONTAINERS. KEEP AWAY FROM CHILDREN.

SPILL/LEAKAGE PROCEDURES:  
THE VISCOUS NATURE OF THIS PRODUCT MAKES SPILLS UNLIKELY. SCOOP UP THE MATERIAL AND RETURN TO ITS ORIGINAL CONTAINER, OR USE AN OIL ABSORBENT MATERIAL AND DISPOSE OF PROPERLY.

WASTE DISPOSAL:  
DISPOSE OF IN A RESPONSIBLE MANNER. FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES. DO NOT DISCHARGE INTO SEWERS OR WATERWAYS. INCINERATION IS THE PREFERRED METHOD OF DISPOSAL, ALTHOUGH IT MAY BE LANDFILLED AT AN APPROVED FACILITY.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:  
NORMALLY NOT REQUIRED. IF THIS PRODUCT IS BEING USED IN HIGH TEMPERATURE APPLICATIONS WHERE THE PRODUCT "SMOKES", USE A LOCAL EXHAUST OR VENTILATE THE AREA TO MAINTAIN THE AIR QUALITY. A "N.I.O.S.H." APPROVED ORGANIC VAPOR RESPIRATOR IS ALSO ACCEPTABLE.

PROTECTIVE GLOVES:  
NORMALLY NOT REQUIRED UNLESS PROLONGED OR REPEATED SKIN CONTACT IS EXPECTED, THEN USE A LATEX OR NEOPRENE GLOVES.

EYE PROTECTION: SAFETY GLASSES ARE RECOMMENDED.

WORK/HYGIENIC PRACTICES:  
USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING.

SECTION IX - REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65: NO  
RCRA: NO  
OZONE DEPLETING SUBSTANCES: NONE  
DOT SHIPPING CLASS: NOT HAZARDOUS  
SARA TITLE III: NO  
TASCA INVENTORY: ALL INGREDIENTS LISTED  
CERCLA: NO  
N.F.P.A. RATING:  
H-1  
F-1  
R-0

SECTION X - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE,  
HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE  
DATA OR THE RESULTS OBTAINED FROM THE USE OF THIS PRODUCT. THEREFORE,  
BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE  
ASSUME NO LIABILITY FOR IT'S USE.

DATE PREPARED: 4/15/02