



SAFETY DATA SHEET

Issuing Date 21-Nov-2013

Revision Date 01-Aug-2014

Revision Number 1

12/4/2018

1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND THE COMPANY/ UNDER TAKING

GHS product identifier

Product Name

Ru-Glyde

Other means of identification

Product Code(s)

RG-18, RG-18BK, RG-18CT, RG-18MY, RG-20, RG-20BK, RG-20MY, RG-55, RG-55BK, RGC-18, RGC-20

Synonyms

Tire Mounting Lubricant

Napa Ruglyde Rubber
Lubricant #8272511

Recommended use of the chemical and restrictions on use

Recommended Use

Tire Mounting and Rubber Lubricant

Uses advised against

No information available

Supplier's details

Supplier Address

AGS Company
P.O. Box 729
Muskegon, MI
49443
TEL: 800-253-0403

Emergency telephone number

Emergency Telephone
Number

800-255-3924

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Acute Oral Toxicity	Category 4
Acute Inhalation Toxicity - Dusts and Mists	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1A

GHS Label elements, including precautionary statements

Emergency Overview**Signal Word****Danger****Hazard Statements**

- Harmful if swallowed
- Harmful if inhaled
- Causes skin irritation
- Causes serious eye irritation
- May cause cancer
- May damage fertility or the unborn child

**Appearance** Tea colored**Physical State** Liquid.**Odor** Odorless**Precautionary Statements****Prevention**

- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Wash face, hands and any exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion

- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- Rinse mouth.

Storage

- Store locked up.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

No information available.

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Tire Mounting Lubricant

Chemical Name	CAS-No	Weight %
Potassium hydroxide	1310-58-3	7.08
Sodium dichromate, dihydrate	7789-12-0	6.93
Ethylene glycol	107-21-1	2.28
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	0.16

4. FIRST AID MEASURES**Description of necessary first-aid measures**

Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin Contact	Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and persists. Remove and wash contaminated clothing before re-use.
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if exposed or you feel unwell.
Ingestion	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Most important symptoms/effects, acute and delayed**Most Important Symptoms/Effects** Irritation.**Indication of immediate medical attention and special treatment needed, if necessary****Notes to Physician** Treat symptomatically.**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media None**Specific Hazards Arising from the Chemical**

Containers may explode when heated.

Hazardous Combustion Products Sodium oxides. Potassium oxides.**Explosion Data****Sensitivity to Mechanical Impact**

None.

Sensitivity to Static Discharge

None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

Methods for Containment Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Use personal protective equipment. Sweep up and shovel into suitable containers for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE**Precautions for safe handling**

Handling Ensure adequate ventilation. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Avoid breathing vapors or mists. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible Products Hydrazine, Acids, Halogenated compounds, Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Sodium dichromate, dihydrate 7789-12-0	TWA: 0.05 mg/m ³ Cr	(vacated) Ceiling: 0.1 mg/m ³ Ceiling: 0.1 mg/m ³ CrO ₃ applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect	IDLH: 15 mg/m ³ Cr(VI) TWA: 0.001 mg/m ³ Cr
Ethylene glycol 107-21-1	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0	TWA: 5 mg/m ³ , as oil mist, mineral STEL: TWA: 10 mg/m ³ , as oil mist, mineral	TWA: 5 mg/m ³ , as oil mist, mineral	-
Triethanolamine 102-71-6	TWA: 5 mg/m ³	-	-

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Tightly fitting safety goggles.
Skin and Body Protection	Protective gloves.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene Measures	Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Appearance	Tea colored
Odor	Odorless	Odor Threshold	No information available
<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>	
pH	9.6	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	100 °C / 212 °F	None known	
Flash Point	No data available	None known	
Evaporation rate	Slower than Butyl Acetate	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		
Vapor Pressure	No data available	None known	
Vapor Density	Heavier than air	Air = 1	
Specific Gravity	1.01	None known	
Water Solubility	Completely soluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition Temperature	No data available	None known	
Decomposition Temperature	No data available	None known	
Viscosity	No data available	None known	
Flammable Properties	Not flammable		
Explosive Properties	No data available		
Oxidizing Properties	No data available		
<u>Other information</u>			
VOC Content (%)	No data available		

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Hydrazine, Acids, Halogenated compounds, Strong oxidizing agents.

Hazardous decomposition products

Sodium oxides. Potassium oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	Harmful by inhalation.
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation.
Ingestion	Harmful if swallowed.

Component Information**Symptoms related to the physical, chemical and toxicological characteristics**

Symptoms	Irritation
-----------------	------------

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	Petroleum products are known to cause cancer because of carcinogenic components (e.g. benzene, DMSO). These carcinogenic components are typically found in crude petroleum products and are removed through the refinement process.

Chemical Name	ACGIH	IARC	NTP	OSHA
Sodium dichromate, dihydrate	A1	Group 1	Known	
Petroleum distillates, solvent dewaxed heavy paraffinic	A2	Group 1		X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity	No information available.
Developmental Toxicity	May cause harm to the unborn child.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration Hazard	No information available.

Numerical measures of toxicity - Product

Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 618 mg/kg; Acute toxicity estimate

LD50 Dermal 3438 mg/kg; Acute toxicity estimate

Inhalation
dust/mist 1.4 mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Potassium hydroxide 1310-58-3		LC50 96 h: = 80 mg/L static (Gambusia affinis)		
Ethylene glycol 107-21-1	EC50 96 h: 6500 - 13000 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 14 - 18 mL/L static (Oncorhynchus mykiss) LC50 96 h: 40000 - 60000 mg/L static (Pimephales promelas) LC50 96 h: = 16000 mg/L static (Poecilia reticulata) LC50 96 h: = 27540 mg/L static (Lepomis macrochirus) LC50 96 h: = 40761 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 41000 mg/L (Oncorhynchus mykiss)	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50 48 h: = 46300 mg/L (Daphnia magna)
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Triethanolamine 102-71-6	EC50 72 h: = 216 mg/L (Desmodesmus subspicatus) EC50 96 h: = 169 mg/L (Desmodesmus subspicatus)	LC50 96 h: 10600 - 13000 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1000 mg/L static (Pimephales promelas) LC50 96 h: 450 - 1000 mg/L static (Lepomis macrochirus)		EC50 24 h: = 1386 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Potassium hydroxide	0.83
Ethylene glycol	-1.93

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material may be a hazardous waste under 40 CFR 261, when discarded.

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT	Not regulated
TDG	Not regulated
MEX	Not regulated.
ICAO	Not regulated
IATA	Not regulated.
IMDG/IMO	Not regulated

RID	Not regulated
ADR	Not regulated
ADN	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethylene glycol	107-21-1	2.28	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium hydroxide	1000 lb			X
Sodium dichromate, dihydrate		X		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Potassium hydroxide	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Ethylene glycol	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Sodium dichromate, dihydrate	7789-12-0	Carcinogen Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Potassium hydroxide	X	X	X		X
Sodium dichromate, dihydrate			X	X	X

Ethylene glycol	X	X	X	X	X
-----------------	---	---	---	---	---

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 0	Physical Hazard 0	Personal Protection X

**Indicates a chronic health hazard.*

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 21-Nov-2013
Revision Date 01-Aug-2014
Revision Note (M)SDS sections updated: 3.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet