


MATERIAL SAFETY DATA SHEET

XYLENE

Page: 1

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZ.	0
PPE	G



Printed: 12/14/2005
Revision: 06/13/2005
Supersedes Revision: 06/10/2005

1. Product and Company Identification

Product Code: CXY24
Product Name: XYLENE
Reference #: 1655
Manufacturer Information
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Phone Number: (901)775-0100
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Web site address: www.wmbarr.com

2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Percentage	OSHA TWA	ACGIH TWA	Other Limits
1. Xylene (mixed isomers)	1330-20-7	95.0 -100.0 %	100 ppm	100 ppm	No data.
Hazardous Components (Chemical Name)	RTECS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Xylene (mixed isomers)	ZE2100000	500 ppm/(10min)	300 ppm	150 ppm	No data.

3. Hazards Identification

Emergency Overview

Danger! Flammable. Keep away from heat, sparks, flame and all other sources of ignition. Vapors may cause flash fire or ignite explosively. Vapors may travel long distances to other areas and rooms away from work site. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and until all vapors are gone from the work site and all areas away from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Health Hazards (Acute and Chronic)

Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness, headache, irritation of respiratory tract, weakness, drowsiness, depression of central nervous system, and watering of eyes. Severe overexposure may cause unconsciousness, anesthesia, irregular heartbeat, and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Acute Exposure Effects:

This product is a skin irritant. It may be absorbed through the skin. It may cause irritation, dermatitis, drying of skin, and numbness in fingers and arms. May increase severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. It may cause irritation, redness, stinging, tearing, excessive swelling of the conjunctiva; and or excessive blinking.

Ingestion Acute Exposure Effects:

Harmful or fatal if swallowed. May cause nausea, vomiting, gastrointestinal irritation, or diarrhea.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. May cause skin irritation, permanent central nervous system changes, kidney damage, and liver damage.

Signs and Symptoms Of Exposure

No data available.

Medical Conditions Generally Aggravated By Exposure

Diseases of the skin, liver, and kidneys.

OSHA Hazard Classes:

HEALTH HAZARDS : N/E

PHYSICAL HAZARDS : N/E

TARGET ORGANS & EFFECTS: N/E

4. First Aid Measures

Emergency and First Aid Procedures

Inhalation:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

Skin Contact:

Irritation may result. Immediately wash with soap and water.

Eye Contact:

Immediately flush with water, remove any contact lenses, continue flushing with water for at least 15 minutes, then get medical attention.

Ingestion:

Do not induce vomiting. Call you local poison control center, hospital emergency room, or physician immediately for instructions.

Note to Physician

Call your local poison control center for further information.

5. Fire Fighting Measures

Flammability Classification:

OSHA Class IC

Flash Pt:

82.00 F Method Used: SCC

Explosive Limits:

LEL: 1.00 UEL: No data.

Autoignition Pt:

No data.

Special Fire Fighting Procedures

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spay to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Unusual Fire and Explosion Hazards

No data available.

Extinguishing Media

Use carbon dioxide, dry powder, or foam.

Unsuitable Extinguishing Media

No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Cleanup:

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area.

Small Spills:

Take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large Spills:

Dike far ahead of spill for later disposal.

7. Handling and Storage

Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. Exposure Controls/Personal Protection

Respiratory Equipment (Specify Type)

For OSHA controlled work place and other regular users --Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provided protection against vapors.

Eye Protection

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

Protective Gloves

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

Other Protective Clothing

Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

Ventilation

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms, or small enclosed areas. Whenever possible, use outdoors in an open area. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately. If the work area is not well ventilated, then do not use this product. A dust mask does not provide protection against vapors.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid
Melting Point: No data.
Boiling Point: > 279.00 F
Autoignition Pt: No data.
Flash Pt: 82.00 F Method: SCC
Explosive Limits: LEL: 1.00 UEL: No data.
Specific Gravity: 0.000000
Bulk Density: 7.180 LB/GA
Vapor Pressure: No data.
Vapor Density: No data.
Evaporation Rate: No data.
Solubility in Water: No data.
Percent Volatile: 99.999 % by weight.
VOC / Volume: 880.0000 G/L
Corrosion Rate: No data.
pH: No data.

Appearance and Odor

No data available.

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability

No data available.

Incompatibility - Materials To Avoid

Incompatible with strong oxidizing agents.

Hazardous Decomposition Or Byproducts

Decomposition may produce carbon monoxide and carbon dioxide.

Hazardous Polymerization: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Polymerization

No data available.

11. Toxicological Information

Toxicological Information

No data available.

Carcinogenicity/Other Information

No data available.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. Ecological Information

Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method

Dispose in accordance with local, state, and federal regulations.

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name

No data available.

15. Regulatory Information

US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Xylene (mixed isomers)	1330-20-7	No	Yes 100 LB	Yes	Yes

US EPA CAA, CWA, TSCA

Hazardous Components (Chemical Name)	CAS #	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Xylene (mixed isomers)	1330-20-7	HAP	Yes	No	No

SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

- Sec.302:** EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. * indicates 10000 LB TPQ if not volatile.
- Sec.304:** EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. ** indicates statutory RQ.
- Sec.313:** EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.
- Sec.110:** EPA SARA 110 Superfund Site Priority Contaminant List

TSCA (Toxic Substances Control Act) Lists:

- 5A(2):** Chemical Subject to Significant New Rules (SNURS)
- 6A:** Commercial Chemical Control Rules
- 8A:** Toxic Substances Subject To Information Rules on Production
- 8A CAIR:** Comprehensive Assessment Information Rules - (CAIR)
- 8A PAIR:** Preliminary Assessment Information Rules - (PAIR)
- 8C:** Records of Allegations of Significant Adverse Reactions
- 8D:** Health and Safety Data Reporting Rules
- 8D TERM:** Health and Safety Data Reporting Rule Terminations

Other Important Lists:

- CWA NPDES:** EPA Clean Water Act NPDES Permit Chemical
- CAA HAP:** EPA Clean Air Act Hazardous Air Pollutant
- CAA ODC:** EPA Clean Air Act Ozone Depleting Chemical (1=CFC, 2=HCFC)
- CA PROP 65:** California Proposition 65

EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

- Yes No Acute (immediate) Health Hazard
- Yes No Chronic (delayed) Health Hazard
- Yes No Fire Hazard
- Yes No Reactive Hazard
- Yes No Sudden Release of Pressure Hazard

16. Other Information

Company Policy or Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.